

P R I M A R E

THE SOUND AND VISION OF SCANDINAVIA

Design Brief – I15 Prisma MK2 Integrated Amplifier



I15 Prisma MK2 is an integrated amplifier and network player – capable of providing exemplary performance whether the source is analog or digital, stored or streamed, wired or wireless.

Continuing a Primare tradition of delivering astonishing performance from compact and elegant devices for easy installation into virtually any living environment, **I15 Prisma MK2's** three-quarter sized cabinet offers even greater possibilities for providing the highest quality music performance and access to any and every room in the house.

I15 Prisma MK2 provides 60 watts of output power per channel, digital to analog conversion with up to PCM 384kHz and DSD 128 capabilities, as well as complete digital media access and system management by way of the Prisma connectivity and control technology.

Prisma provides multi-room/multi-zone connectivity and control for playback of stored and streamed media, wired or wireless, all managed from any mobile device through a dedicated system control app. In addition to Bluetooth, AirPlay, and Spotify Connect, **Prisma** features Chromecast built-in, a unique streaming portal allowing effortless direct connection to hundreds of streaming applications for the best possible performance and user experience.



Contents

- Design Philosophy
- Amplifier Technology
- Digital to Analog Conversion Technology
- Prisma Connectivity and Control Technology
- Specifications

Design philosophy

All of Primare designs are a result of our Practical Design Approach, resulting in a focus on two fundamental design elements:

1. Thoroughly implemented power supply designs – so that all elements of any design to operate effortlessly at their fullest effectiveness. Every product and sub-circuit demands unique power supply solutions - a more conventional linear supply or advanced switch mode main supply may work best dependent upon the application, and carefully crafted individual discrete power supplies are strategically inserted into the circuit to deliver power exactly where and how much is needed.
2. Artfully crafted ultra-short signal paths - so that each individual component and sub circuit operates sympathetically to achieve a cohesive whole. Elegant and simple electrical designs are used in even the most complex product, utilizing ultra-short signal paths with all gain in one device whenever possible. Ultimately, this results in fewer, higher quality parts for a reduction in associated distortions and an increase in overall electrical efficiency.

To that end, basic technologies have been selected to realize those benefits:

- 2 and 4-layer double-sided circuit board construction allows for the most direct and efficient layout of circuit components not only for the shortest signal path, but also to more easily achieve a sympathetic layout of circuit and sub-circuit components for best performance.
- Surface mount components are used whenever possible as this allows for direct connection of the circuit device or component to the circuit board trace with the solder being used solely to mechanically hold the part in place. The elimination of the small metal lead or wire at each connection point in a more conventional large scale circuit device or component cumulatively shortens the signal path. Additionally, conventional large scale components demand through hole or “eyelet” construction, limiting direct contact of the component’s lead to the circuit board trace and resulting in the solder providing electrical connection as well as mechanical connection for the device. Neither solder nor the metal used in the leads of most large scale devices provide the best signal transmission, therefore limiting potential performance of even the best designed circuits.
- Class D amplifier technology has many inherent advantages, one of which is the ability to locate the heat sink directly on the circuit board within the amplification module, considerably reducing circuit path length and allowing for the power output devices to be directly connected to the speaker output connection posts.



Amplifier Technology

Input section

Carefully crafted input circuitry utilizes relays for input switching providing better isolation and sound than found in more conventional CMOS (Complementary metal–oxide–semiconductor) switches, and improved 2 x 4 channel balanced mode volume control IC selected for optimal channel balance and low listening level performance.

Control Section

- The latest generation OLED display technology used in the I35 was originally developed for the automobile industry to ensure long life in even the most hostile environments, and improved readability due to greater consistency of color value and brightness level.
- Auto sense input circuitry automatically selects any input source as it is activated.
- C25 IR remote control with completely new, proprietary control codes for faster response and reduced interference.
- RS-232 connection, in addition to being used for component quality control testing of each and every product, allows for the use of whole home system control technologies such as Control 4.
- 12V triggers for coordinated system turn on and turn off.

Control Configuration

Either from the front panel, C25 IR remote control or Prisma app, the I15 Prisma MK2 can be configured to best suit system needs, including:

- Input settings
 - Status – enable or disable the input to make it visible or not, so only those you use are visible for easier input selection
 - Alias – edit the alias, or rename, each input to give it a specific name, for easier identification
 - Auto-sense – enable auto-sense to determine which inputs will be automatically selected when a signal is detected
 - Volume – choose between variable or fixed volume, allowing any input to pass through the preamp stage to connect directly to the amplifier for use of within a home theater system configuration.
Or fixed gain setting allows for any input to be use in a theater or surround sound pass through configuration
 - Input Gain – adjusting the input gain so that all inputs to be at the same relative volume level, and as result the ability to raise or lower overall gain for preferred output volume setting
- Audio Settings
 - Balance – to adjust the output balance between the left and right speaker
 - Startup volume – sets the volume level at a predetermined level upon turn on from standby or at the level when last switched off.
 - Maximum volume – sets the maximum volume
 - Mute volume – sets the output level when muted, from 0 to any preferred setting
 - Digital output – to select between 48kHz and 96kHz settings for the digital output from analog inputs, as some devices in your system might not be compatible with the default 96kHz output.
- General
 - Show inputs – choose between showing all enabled inputs or only those with signal



- Front panel – to lock the front panel to disable all front panel controls
- Auto dim – select the amount of time at which the front panel display will dim
- LED brightness – set the level of display brightness for three specified dim levels
- Standby settings
 - Standby mode – select
 - “normal” standby, which allows any activated input device set to “wake up” enable to wake up the Prisma integrated amp or preamplifier from standby
 - or “Eco” in order for the device to consume less than 0.5W in standby mode, disabling auto wake-up
 - Auto-standby – sets the amount of time without user interface action or signal from last selected source before the device automatically goes into standby
 - Wake up – enables auto-sense to wake up the device from standby upon detecting an input signal source
 - Factory reset – allows for the device to be returned to factory default settings

Amplification Section

The I15 Prisma MK2 employs a specially made Hypex UCD102 amplifier module, fed by our custom heavy duty switch mode power supply and carefully crafted analog input stage, provides a dynamic and detailed sound. The large scale mass production of this module allows us to provide the balanced and coherent sound for which Primare has become known at a more reasonable price than can be achieved with our limited production UFPD 2 amplifier module technology.

Power Supply Section

Given the speed with which the Hypex amplifier module is able to deliver power to the speaker a switch mode power supply was the only choice in that it allows for rapidly varying demand, providing much more stable voltage, with ancillary capacitive storage to meet peak transient burst requirements.

Digital to Analog Conversion (DAC) Technology

In order to allow for playback of virtually any digital source with absolute accuracy and musicality a high performance 32-bit stereo ESS ES9028Q2M reference DAC chipset was selected for the I15 Prisma MK2, which uses the critically acclaimed ESS patented 32-bit HyperStream™ technology capable of delivering a DNR of 129dB and THD+N of -120db S/N, while supporting up to 384kHz PCM and 256/11.2MHz DSD; performance level that will satisfy the most demanding audio enthusiast.



Prisma Connectivity and Control Technology

Prisma provides multi-room/multi-zone connectivity and control for playback of stored and streamed media, wired or wireless, all managed from any mobile device through a dedicated system control app. In addition to Bluetooth®, AirPlay, and Spotify Connect, Prisma features Chromecast built-in, a unique streaming portal allowing effortless direct connection to hundreds of streaming applications for the best possible performance and user experience.

Prisma App, in addition to the configuration settings control listed above, provides:


- Switching of all inputs, analog and digital, stored or streamed
- Playback functions: Play, stop, track forward and back, shuffle play, repeat single or all tracks, volume mute, volume adjustment either by tapping the -/+ icons or sliding your finger across the volume bar
- Multi-room multi-zone control between other Prisma enabled devices
- Search by artist, album, track, and title from stored media
- Complete track information, including file format, bit and sample rate
- Playlist and Queue creation from stored media

Connectivity

- Digital - USB-A
 - Sample rates up to PCM 24/192kHz and DSD 128/5.6mHz
 - File formats: WAV, LPCM, AIFF, FLAC, ALAC, MP3, MP4 (AAC), WMA, OGG, DSD
- Network
 - Wired/LAN – two Ethernet connection ports allow Prisma to act as network switch for flexible wired network system connection options
 - Wireless/WLAN - dual band wireless technology (WLAN IEEE 802.11 a/b/g/n and 802.11 ac compliant)
- Streaming
 - Bluetooth – connects Apple, Android, and Windows devices directly for playback of either streamed or stored content from the associated device with lossy compression. Given the wide availability of this technology and lower resolution capabilities, Bluetooth is an easy way to stream content for informal listening.
 - AirPlay – connects Apple devices over the WiFi network for playback of either streamed or stored content from the associated device with lossless compression. As a result, AirPlay has the capability of playing over greater distances than Bluetooth, and as the Apple Lossless Audio Codec is used to allow streaming quality up to CD quality (44.1 kHz), is appropriate for more critical listening.
 - Spotify Connect – connects any device with the Spotify application over the WiFi network directly to that service, and allows for playback at the highest level offered by the required Premium service (up to 320 kbps).
 - Chromecast built-in - offering the greatest level of connectivity and control options:
 - The Chromecast built-in associated Google Home application connects the Prisma device to your WiFi network for casting hundreds of enabled music streaming services.



- Because it provides a direct connection between the I15 Prisma MK2 and the preferred music service through the network, playback quality is limited only by the quality of resolution provided by that service, meaning the possibility of higher resolution playback from services like TIDAL HiFi and Qobuz (up to 24-bit/96kHz).
- More than one device can be connected at a time, content can be cast to any Chromecast built-in device on the network, and control of all functions can be accomplished from anywhere within the network.
- Automatic Prisma firmware updating through Google Home application.
- Voice control through the Google Home speaker and Google Assistant is anticipated as that system becomes readily available.





I15 Prisma MK2 Specifications

Amplification

Amplifier technology: Hypex UcD102

Output Power: 2x 60W at 8 Ω ; 2x 100W at 4 Ω

Analogue Inputs:

- 1 pair RCA (L & R)
- 1 3.5mm stereo jack

Input Impedance: RCA 9.5 k Ω

Pre Out: 1 pair RCA (L & R)

Output Impedance: 150 Ω

Gain:

- Pre out 16.5 dB
- Speaker out 42.5 dB

Frequency Response:

- Analog: 20Hz – 20kHz -0,5dB
- Digital:
 - 44.1kHz 20Hz – 20kHz +0.1/-0,6dB
 - 96kHz 20Hz – 20kHz +0.1 /-0,2dB
 - 192kHz 20Hz – 20kHz +/- 0.1 dB

THD + N: < 0.05%, 20Hz – 20kHz, 10W at 8 Ω

Signal to Noise:

- >90 dB digital
- >80 dB analog



DAC

Chip set: ES9028Q2M, fast roll-off filter

Digital Inputs

- 3 x Optical/TOSLINK 192 kHz
- 1 x 3.55mm mini-plug: 192 kHz
- 1 x SPDIF/RCA: 192 kHz
- 1 x USB-B: up to 384 kHz/24 bit; DSD 5.6/128

Digital Output: 1 x RCA

- Analog input = 48 kHz out
- Digital input = pass through

Prisma

Audio formats: WAV, LPCM, AIFF, FLAC, ALAC, MP3, MP4 (AAC), WMA, OGG, DSD

WLAN: IEEE 802.11 a/b/g/n/ac compliant; 2.4/5GHz; b, g, n mode

Wired Inputs:

- USB-A: 192 kHz/24 bit; DSD 64/128
- 2 x LAN: 192 kHz/24 bit; DSD 64/128
- WLAN: 192 kHz/24 bit; DSD 64/128

Wireless Inputs:

- Airplay®
- Bluetooth®
- Chromecast built-in®
- Spotify Connect®

General

Control

- C25 system remote control
- RS232 – Control 4
- IR in/out
- Trigger out

Power Consumption:

- Standby: <0.5W
- Operate: <25W

Dimensions (wxdxh):

- 350 x 329 x 73 mm with knobs and connectors
- 350 x 310 x 73 mm without knobs and connectors

Weight: 6.4 kg

Color Options: Black and Titanium

