

HTS



HOME THEATRE SYSTEMS

TANNOY®

TANNOY PERFORMANCE, DESIGNER STYLE

Tannoy HTS is a new breed of loudspeaker offering superb sound and sumptuous, design. With the power and performance to thrill with movies the HTS range integrates Tannoy's high-tech neodymium drivers and WideBand™ tweeter technology in real wood cabinets for a supremely rich and detailed sound. Slim, sleek and unobtrusive each HTS speaker is finished in a luxurious deep gloss black to match today's electronics and blend effortlessly with contemporary décor.



HTS HOME THEATRE SYSTEMS

The HTS range is available in two simple packages. The HTS101 is a discreet, exceptionally compact wall or shelf mount system ideal for smaller spaces. The four satellites utilise a 75mm (3") mid bass driver and a 19mm (3/4") Tannoy WideBand™ tweeter with titanium dome and powerful neodymium magnet system. Housed in rigid wooden cabinets the HTS Satellites integrate seamlessly with the twin mid bass driver HTS Centre channel speaker. The HTS active subwoofer completes the HTS101 package with its 200mm (8") driver and compact cabinet capable of delivering deep bass in any room location.

The potent HTS201 is designed for larger rooms and is ideal for those looking for the best performance for music and movies. This system delivers a larger scale sound and fuller acoustic across the front soundstage with its visually striking HTS Tower speakers. Used as the main front left and right channels, the HTS Towers incorporate twin 75mm (3") mid bass drivers and the 19mm (3/4") HTS tweeter in a larger cabinet to deliver extra punch and dynamic attack. Combined with a pair of HTS Satellites for rear effects, an HTS Centre and the potent HTS Subwoofer, the HTS 201 system delivers a new level of performance and style.





CENTRE & SATELLITES

PERFORMANCE

Recommended amplifier power	25 – 100 Watts (RMS)
Maximum Sensitivity (2.83Volts @ 1m)	87dB
Nominal impedance	8 Ohms
Frequency response (-6dB)	100Hz – 40kHz
Satellite Drivers	HF: 19mm (3/4") titanium WideBand™ dome, with neodymium magnet system LF: 75mm (3") paper cone

Centre Drivers

HF: 19mm (3/4") titanium WideBand™ dome, with neodymium magnet system
LF: 2 x 75mm (3") paper cone

Crossover frequency

3kHz (LF to HF)

Magnetic shielding

Yes

Satellite Weight

1.4kg (3.1lbs)

Satellite Dimensions H x W x D

160mm x 106mm x 142mm (6.3" x 4.2" x 5.6")

Centre Weight

2.3kg (5.1lbs)

Centre Dimensions H x W x D

106mm x 250mm x 166mm (4.2" x 9.8" x 6.6")

Finish

Gloss Black

Supplied accessories

Wall bracket, self adhesive feet

TOWER

PERFORMANCE

Recommended amplifier power	25 – 100 Watts (RMS)
Maximum Sensitivity (2.83Volts @ 1m)	88dB
Nominal impedance	6 Ohms
Frequency response (-6dB)	80Hz – 40kHz
Drivers	HF: 19mm (3/4") titanium WideBand™ dome, with neodymium magnet system LF: 2 x 75mm (3") paper cone

Crossover frequency

3kHz

Magnetic shielding

Yes

Weight

6.2kg (13.7lbs)

Dimensions H x W x D

904mm x 106mm x 167mm (35.6" x 4.2" x 6.6")

Dimensions H x W x D

922mm x 179mm x 225mm (36.3" x 7.1" x 8.9")

(including plinth & grille)

Finish

Gloss Black

Supplied accessories

Floor coupling spikes with floor protective cups, self adhesive feet

SUBWOOFER

PERFORMANCE

Power Output	100 Watts
Frequency Response (-6dB)	29Hz – 200Hz
Crossover Frequency	50Hz – 200Hz, variable control
Driver	200mm (8") paper cone, long throw
Inputs	LFE / Line Input (RCA / phono), or Left & Right speaker level inputs
Power Requirements	115 or 230V AC nominal, 50- 60Hz (switchable), 60VA maximum

Fuse Rating

AC 110 - 120V T1.6AL 250V

Additional Features

AC 220 - 240V T800mAL 250V
Energy saving AUTO power function
Switchable phase, 0 or 180 degrees
Volume and crossover frequency controls

Magnetic Shielding

No

Weight

10.0kg (24.3lbs)

Dimensions H x W x D

420mm x 275mm x 370mm (16.5" x 10.8" x 14.6")

(including feet)

Finish

Gloss Black

Supplied Accessories

Country specific mains cable (cord)

Tannoy United Kingdom	T: 00 44 (0) 1236 420199	E: enquiries@tannoy.com
Tannoy Deutschland	T: 00 49 (180) 1111 881	E: anfragen@tannoy.com
Tannoy Middle East	T: 00 971 (04) 4401208	E: enquiries@tannoy.com
TCIGroup International	T: 00 45 8742 7000	E: info@tcgroup-international.com
TCIGroup Americas	T: 00 1 (519) 745 1158	E: info@tcgroup-americas.com

Tannoy adopts a policy of continuous improvement and product specification is subject to change.