

Amp Box S

Stereo power amplifier

- Ultra compact & audiophile
- **NEW!** advanced amplifier module
- **NEW!** More power and further improved performance
- Stereo input (RCA)
- Gold plated speaker sockets
- Suitable for Banana/Spade/Pin/bare wire
- Trigger input
- Trigger output for further Amp Box S
- Metal casing protects against vibration and interference
- On/Off front-sided
- Faceplate silver or black

Technical data

Power output	2 x 25W/35W @ 8/4 ohms
Frequency response	5Hz - 20kHz (+ 0dB, - 0,5dB)
Channel separation	> 40dB @ 20kHz
Signal-to-noise ratio	> -100dB (IEC -A)
THD	< 0,05% @ 10W
Gain	22dB
Input	1 pair RCA sockets
Input sensitivity	1V
Input impedance	47kohm
Speaker sockets	4mm Ø Banana sockets, spades. Pins or bare wire
Trigger 12V DC	In&Out, 2-pole jack socket Ø 2,5mm
External power supply	20V/3A DC (peak 7A DC); 100 - 240V, 50/60Hz
Standby power consumption	< 1 Watt
Dimensions W x H x D	103 x 36 x 104 (122mm with sockets)
Weight	670g without power supply



Retail price
249,00 €

Ultra compact power amplifier - efficient & audiophile!

A ultra high-efficiency Bi-Phase PWM (Pulse Wave Modulation) circuit with SMD parts incorporates 35 years of R&D and gives outstanding audio performance, while staying cool on the outside. It fulfills our demand for high resolution with superior micro dynamics and room-filling power. Sound quality is aimed to be as close as possible to Class A tube amplifiers with their liquid and lifelike presentation. The Amp Box S is micro-sized and therefore allows easy placement and can be switched on & off remotely via a trigger signal. A 45cm power-on cable is supplied for this purpose. For Bi- or Tri-amplification use, the remote power-on signal can be relayed to further units.



< Front view
(black faceplate)

rear view >

connections

