

Pre Box DS

Stereo Line preamplifier

- **NEW!** improved circuitry with even less noise
- **NEW!** Volume control through relays (64 steps, 1 dB)
- **NEW!** 4 line level inputs
- **NEW!** relays switching of inputs
- 1x Pre-Out, 1x Subwoofer-Out, 1x Record-Out
- Extremely low output impedance for low loss with long cables
- IR remote control
- Trigger switching of power amplifiers
- Big elegant control display
- Metal casing protects against vibration and interference
- Available in black and silver

Technical data

Frequency response	20Hz - 20kHz (- 0,3/- 0,1 dB)
Signal to noise ratio	-100dB (IEC -A)
THD	0,0035%
Gain	13dB
Pre out	1 Pre-Out, 1 Sub-Out, 1x Rec-Out (RCA)
Output voltage	1V at 1kHz
Line-level inputs	4 pairs RCA/phono sockets
Input impedance	10kohms
Trigger	12 Volt DC switching voltage
Trigger output	2-pole 2,5mm Ø co-axial jack
Outboard power supply	18V/500mA DC suitable for your country's mains supply
Standby power consumption	< 1 watt
Dimensions W x H x D	103 x 72 x 144mm (150 with sockets)
Weight	1100g without power supply



Audiophile preamplifier with 4 line inputs!

The heart of the Pre Box DS is a pure single-ended Class-A Outputstage-Design, a real High-End solution. The highly shielded metal chassis effectively rejects any vibration and electromagnetic noise. 12-volts Trigger switching is provided so other components connected can be power activated with the Pre Box DS. IR remote comes with Pre Box DS to switch inputs and adjust volume. Former test-darling Pre Box SE had only one weakness: very low level of hiss, when used with low-level input signals. With a new circuitry plus relais-controlled volume regulation and input selection this minor problem completely disappears with Pre Box DS. No other preamplifier ever before offered such high effort in audio technology in this price range. As a result this ultra dynamic preamplifier is an outstanding sound marvel!



< black version

Rear view >

- ◇ Inputs
- ◇ Pre-Out
- ◇ Rec-Out
- ◇ Sub-Out
- ◇ Power

