



SoundWare S

Home Theater Speakers

Smart features



Small speakers provide big, high performance sound




BassTrac® circuitry for deep, powerful bass without distortion



Included wall brackets can be positioned at almost any angle

- Unique SoundWare shape allows for maximum placement flexibility
- Durable high-gloss finish for a modern look
- Easy-guide wire channels for fast hook-up
- 200-watt 10" subwoofer delivers powerful, room-filling bass
- Optional SoundWare S Satellite Speakers for 7.1 are available



SoundWare S

Home Theater Speakers

Designed for surround sound

The SoundWare S compact 5.1 speaker package brings a new level of style and substance to the fast-growing surround sound home entertainment category. The speaker system provides rich, room-filling surround sound, while complementing virtually any décor in a stylish yet subtle manner.

The system's five ultra-compact, high gloss SoundWare S satellites are real two-way speakers, each features a high-performance 3½-inch (89mm) woofer and a ¾-inch (19mm) tweeter. The contoured-rectangle subwoofer features a 200-watt (300watts peak) amplifier and 10-inch (254mm) DCD driver. Wall brackets are included for easy installation of all five satellite speakers. To create a complete home theater system, use the SoundWare S Home Theater Speakers with an AV receiver, Blu-ray™ or DVD Player, and your TV.


10" 200-watt Powered Subwoofer

- Graphite injected polymer woofer utilizes Deep Channel® Design (DCD) for more bass from less amplifier power
- BassTrac® circuitry for tight, distortion-free bass at all output levels
- 200-watt (300 watts Peak) amplifier for powerful low frequency reproduction
- Acoustically tuned port for improved bass output

system includes five satellite speakers and one powered subwoofer



Specifications	S Satellite	S Subwoofer
Frequency Response:	132Hz – 20kHz	32HZ - 135Hz
Recommended Amplifier	10 – 125 watts	—
Sensitivity:	87dB [SPL/2.8v at 1m]	—
Nominal Impedance:	8 ohms	—
Crossover Frequency:	4200Hz	60Hz - 135Hz 24dB/octave variable lowpass
Amplifier Output:		200 watts RMS, (300 watts Peak); BassTrac® circuitry eliminates distortion
Woofer:	3½" (89mm)	10" (254mm) DCD
Tweeter:	¾" (19mm)	—
Dimensions: (H x W x D)	5½ x 5½ x 5½" (138 x 138 x 143mm)	13¾ x 12¾ x 17¾" (339 x 315 x 435mm)



At an angle



On any surface



In a corner

300 Jubilee Drive, Peabody, MA 01960 • bostonacoustics.com

© 2011. All rights reserved. Boston, Boston Acoustics, B/A ellipse symbol, BassTrac, and Deep Channel are registered trademarks of Boston Acoustics, Inc. Blu-ray is a trademark of the Blu-ray Disc Association.

